Consideration and allowance of the present application is most respectfully requested.

Respectfully submitted,

Michael J. Striker
Attorney for Applicant(s)
Reg. No. 27233

19. A wiper blade for windows, in particular of motor vehicles, with at least one support element (12), a wiper strip (14), and a connecting device (16) for a wiper arm (18), wherein the support element (12) is an elongated, flat bar to which the wiper strip (14) and the connecting device (16) are attached, characterized in that the support element (12) has a cross sectional profile in which

$$\frac{F_{wf} * L^2}{48 * E * I_{zz}} < 0.009,$$

where F_{wf} is the contact force exerted on the wiper blade by the wiper arm (18) or is the contact force for which the wiper blade was originally designed, L is the length of the support element (12), E is the elasticity modulus of the support element (12), and I_{zz} is the moment of inertia of the cross sectional profile around the z-axis perpendicular to an s-axis, which adapts along with the support element (12), and perpendicular to a y-axis.

20. The wiper blade according to claim 19, characterized in that

$$\frac{F_{wf} * L^2}{48 * E * I_{zz}} < 0.005.$$

21. The wiper blade according to claim 19, characterized in that the support element (12) has an <u>essentially</u> rectangular cross sectional profile (40), with an essentially constant width b and an essentially constant thickness d.

22. The wiper blade according to claim 19, characterized in that the support element (12) is comprised of at least two individual bars (42, 44) and that the widths (b1, b2) of the individual bars (42, 44) add up to a total width b.

23. The wiper blade according to claim 19, characterized in that the width b and the thickness d of the support element (12) are selected so that

$$\frac{F_{wf} * L^2}{4 * E * d * b^3} < 0.009 .$$

24. The wiper blade according to claim 19, characterized in that the width b and the thickness d of the flat bar are selected so that

$$\frac{F_{wf} * L^2}{4 * E * d * b^3} < 0.005 .$$

25. A wiper blade for windows, in particular of motor vehicles, with at least one support element (12), a wiper strip (14), and a connecting device (16) for a wiper arm (18), wherein the support element (12) is an elongated,

flat bar to which the wiper strip (14) and the connecting device (16) are attached, in particular according to one of the preceding claims, characterized in that the support element (12) has a cross sectional profile (40) which produces a lateral deflection angle of at least one of the support element ends in relation to the longitudinal span of the support element of $\gamma < 0.5°$, in particular $< 0.3°$ against the window (26), when the wiper blade is moved on the window (26) lateral to its longitudinal span, and the friction coefficient between the window (26) and the wiper strip (14) is approximately 1.

26. A wiper blade for windows, in particular of motor vehicles, with at least one support element (12), a wiper strip (14), and a connecting device (16) for a wiper arm (18), wherein the support element (12) is an elongated, flat bar to which the wiper strip (14) and the connecting device (16) are attached, in particular according to one of the preceding claims, characterized in that the support element has a length L, a width b, and a thickness d such that

$$.20L^2 < bd^2 < 40L^2$$

in which L is given in meters and b and d are given in millimeters.

27. The wiper blade according to claim 26, characterized in that the support element is comprised of two spring bars whose widths are added to each other.

28. A wiper blade for windows (15), in particular of motor
vehicles, with at least one elongated support element (12),
a wiper strip (14), and a connecting device (16) for a
wiper arm (18) which presses the wiper blade (10) against
the window (15) in an operating position, wherein the
support element (12) is an elongated, flat bar to which the
wiper strip (14) and the connecting device (16) are
attached, and which has a curvature when it is not loaded
by the wiper arm (18), in particular according to one of
the preceding claims, characterized in that the curvature
along a coordinate (s), which follows the longitudinal span
of the support element (12), has values such that the
second derivative of the curvature as a function of this
coordinate (s) is essentially proportional to a contact
force distribution p (s), which is produced when the wiper
blade (10) is pressed against a flat window (15), and that
the contact force distribution decreases toward at least
one end.

29. The wiper blade according to claim 28, characterized in
that

$$\frac{d^2 K(s)}{ds^2} = \frac{d^2 M(s)}{ds^2} * E * I = \frac{p(s)}{E * I}$$

s   =   coordinate along the support element
K(s) =   curvature of the support element
M(s) =   bending moment.
E   =   elasticity modulus
I   =   surface moment of inertia of the support element
in relation to the neutral axis

p(s) =   specific force per unit length = contact force
distribution.

30. A wiper blade for windows (15), in particular of motor
vehicles, with at least one elongated support element (12),
a wiper strip (14), and a connecting device (16) for a
wiper arm (18) which presses the wiper blade (10) against
the window (15) in an operating position, wherein the
support element (12) is an elongated, flat bar to which the
wiper strip (14) and the connecting device (16) are.
attached, and which has a curvature when it is not loaded
by the wiper arm (18), in particular according to one· of
the preceding claims, characterized in that the curvature
along a coordinate (s), which follows the longitudinal span
of the support element (12), has values such that the
second derivative of the curvature as a function of this
coordinate (s) minus the second derivative of the curvature
of the window (15) decreases from a middle region (40)
toward the ends. .

31. The wiper blade according to claim 30, characterized in
that the middle region (40) is the location of the
connecting device (16). .

32. The wiper blade according to one of claim 30,
characterized in that

$$\frac{d^2K(s)}{ds^2} = \frac{p(s)}{E*I} + \frac{d^2K_{window}(s)}{ds^2}$$

s   =   coordinate along the support element

K(s) =   curvature of the support element

M(s) =   bending moment

E   =   elasticity modulus

I   =   surface moment of inertia of the support element
in relation to the neutral axis

p(s) =   specific force per unit length = contact force
distribution.

33. A wiper blade for windows (15), in particular of motor
vehicles, with at least one elongated support element (12),
a wiper strip (14), and a connecting device (16) for a
wiper arm (18) which presses the wiper blade (10) against
the window (15) in an operating position, wherein the
support element (12) is an elongated, flat bar to which the
wiper strip (14) and the connecting device (16) are
attached, and which has a curvature when it is not loaded
by the wiper arm (18), in particular according to one of
the preceding claims, characterized in that the curvature
along a coordinate (s), which follows the longitudinal span
of the support element (12), has values such that the
contact force distribution p (s), which prevails when the
wiper blade (10) is pressed against a flat window (15) is
greater in a region (40) approximately halfway between the
center and the end of the wiper blade (10) than it is at
the end of the wiper blade (10).

34. A wiper blade for windows (15), in particular of motor
vehicles, with at least one elongated support element (12),
a wiper strip (14), and a connecting device (16) for a
wiper arm (18) which presses the wiper blade (10) against
the window (15) in an operating position, wherein the

support element (12) is an elongated, flat bar to which the wiper strip (14) and the connecting device (16) are attached, and which has a curvature when it is not loaded by the wiper arm (18), in particular according to one of the preceding claims, characterized in that the curvature along a coordinate (s), which follows the longitudinal span of the support element (12), has values such that the contact force distribution p (s), which prevails when the wiper blade (10) is pressed against the window (15) to be wiped, is greater in a region (40) approximately halfway between the center and the end of the wiper blade (10) than it is at the end of the wiper blade (10).

35. A method for producing a wiper blade according to claim 19, characterized by means of the following process steps: determination of the length L and adapted contact force F_{wf} required for the window to be wiped,
determination of the width b and the thickness d,
determination of the curvature progression K(s),
bending of the support element,
connection of the support element, wiper strip, and connecting device.

36. The method according to claim 35, characterized by means of the following process steps:
- determination of the length L and the cross sectional profile, particularly the width b and the thickness d by means of experimental values,
- determination of a contact force F_{wf} and a contact force distribution p for a flat window, which assures a favorable wiping quality, likewise by means of experimental values,

- measurement of the curvature progression K_{window} of the window,
- double derivation of this curvature progression K_{window} of the window as a function of a coordinate that adapts along with the curvature,
- calculation of the second derivative of the curvature progression $K(s)$ of the support element according to the above relation,
- double integration yields the desired curvature progression $K(s)$ of the support element.